


## MEDO 40 EL

LED indoor recessed ceiling light, frameless version, white, 3000/4000K

The recessed version of the MEDO series fits into every room concept seamlessly thanks to its understated design. The MEDO Frameless combines with the ceiling in a charming way. The light colour can be easily switched between 3000K and 4000K prior to installation using a switch. The integrated premium LED module provides an even lighting effect. Supplemented by an additional driver, the TRIAC recessed variant becomes dimmable and can be integrated in DALI systems.



## TECHNICAL DATA

Item no.:	1001902
Secondary power / secondary voltage	700 mA/V
Height	9.5 cm
Diameter	38.0 cm
Installation diameter	39.0 cm
Installation depth	13.0 cm
Net weight	1.896 kg
Gross weight	2.801 kg
IP Code	IP 20
Safety class	III
Assembly	Recessed
Assembly details	Ceiling
Wattage	28 W
Lumen	3100 / 3300 lm
Colour temperature	3000/4000 Kelvin
Beam angle	105 °
Color	white
CRI	>80
UGR ≤	25
Binning	3
LXXBXX data	70/50
Service life	25000 h

Maximum ambient temperature	40 °C
BIG WHITE Page	455

## Accessories

1002424	LED driver MEDO 400 dimmable DALI/1-10V
464168	LED DRIVER , 40W, 700mA, incl. strain relief

## Notes

---



---



---



---



---